

Safety Data Sheet

ULTRAFLEX LFT WHITE

Safety Data Sheet dated: 4/16/2015 - version 1

Date of first edition: 4/16/2015

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: ULTRAFLEX LFT WHITE

Recommended use of the chemical and restrictions on use

Recommended use: Adhesive Restrictions on use: N.A.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Emergency 24 hour numbers: (USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-613-996-6666

2. HAZARD(S) IDENTIFICATION







Classification of the chemical

Classification of the chemical

Skin Corr. 1B Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

Description

Skin Sens. 1 May cause an allergic skin reaction. Carc. 1A May cause cancer if inhaled. STOT SE 3 May cause respiratory irritation.

STOT RE 1 Causes damage to organs through prolonged or repeated exposure if inhaled.

Label elements

Symbols:

Code H314



Danger	
Danger	

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350.A	May cause cancer if inhaled.
H372.A	Causes damage to organs through prolonged or repeated exposure if inhaled.
Code	Description
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260.B	Do not breathe dust.
P264.3	Wash skin thoroughly after handling.
P270	Do no eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

ULTRAFLEX LFT WHITE Date 4/16/2015 Production Name Page n. 1 of 8 P303+P361+P353.1 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501.A.1 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Quantity	Name	Ident. Numb.	Classification
40-60 %	Silica Sand	CAS:14808-60-7	Carc. 1A, H350.A; STOT RE 1, H372.A
20-40 %	Portland cement	CAS:65997-15-1	STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Irrit. 2, H315
1-5 %	Gypsum	CAS:13397-24-5	STOT SE 3, H335

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Date 4/16/2015 Production Name ULTRAFLEX LFT WHITE Page n. 2 of 8

Burning produces heavy smoke. Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

List of components with OEL value

Component	OEL Type Country	Ceiling	Long Term mg/m3	Long Term	Short Term mg/m3	Short Term	Behaviour	Note
Silica Sand	ACGIH		0,025		•			A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;
Portland cement	OSHA		15					cancer, paintenary horosis,
	OSHA		5					
	ACGIH		1					A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma;
Gypsum	OSHA		15					cyp.too,ucuu,
	OSHA		5					
	ACGIH		10					nasal symptoms (listed under Calcium sulfate);

Appropriate engineering controls: N.A.

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Date 4/16/2015 Production Name ULTRAFLEX LFT WHITE Page n. 3 of 8

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State: Solid

Appearance and colour: Powder

Odour: N.A.

Odour threshold: N.A.

pH in Water Dispersion: 12.00

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: Not Applicable Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A. Vapour pressure: N.A. Relative density: N.A. Solubility in water: N.A. Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.
Oxidizing properties: N.A.
Solid/gas flammability: N.A.

Other information

Substance Groups relevant properties N.A.

Miscibility: N.A. Fat Solubility: N.A. Conductivity: N.A.

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not Available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

Silica Sand a) acute toxicity LD50 Oral Rat = 500mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

a) acute toxicity

b) skin corrosion/irritation

Date 4/16/2015 Production Name ULTRAFLEX LFT WHITE Page n. 4 of 8

- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

Substance(s) listed on the IARC Monographs:

Silica Sand Group 1

Substance(s) listed as OSHA Carcinogen(s):

Silica Sand

Substance(s) listed as NIOSH Carcinogen(s):

Silica Sand

Substance(s) listed on the NTP report on Carcinogens:

Silica Sand

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Quantity Component Ident. Numb. Ecotox Infos

40-60 % Silica Sand CAS: 14808-60-7 LC50 a) Aquatic acute toxicity carp> 10000,0000mg/L 72h

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

ADR-UN number: N.A.
DOT-UN Number: N.A.
IATA-Un number: N.A.
IMDG-Un number: N.A.

UN proper shipping name Transport hazard class(es)

ADR-Class: N.A.
DOT Hazard Class: N.A.
IATA-Class: N.A.
IMDG-Class: N.A.

Packing group

ADR-Packing Group: N.A. DOT-Packing group: N.A. IATA-Packing group: N.A. IMDG-Packing group: N.A.

Environmental hazards

Date 4/16/2015 Production Name ULTRAFLEX LFT WHITE Page n. 5 of 8

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

Special precautions

Department of Transportation (DOT):

N.A.

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A.

Sea (IMDG):

N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Silica Sand is listed in TSCA Section 8b

Portland cement is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

no substances listed

Section 304 - Hazardous substances:

no substances listed

Section 313 - Toxic chemical list:

no substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

no substances listed

CAA - Clean Air Act

CAA listed substances:

no substances listed

CWA - Clean Water Act

CWA listed substances:

no substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Silica Sand Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Silica Sand

Portland cement

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Silica Sand

Date 4/16/2015 Production Name ULTRAFLEX LFT WHITE Page n. 6 of 8

Gypsum

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Silica Sand
Portland cement
Gypsum

16. OTHER INFORMATION

Code	Description
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350.A	May cause cancer if inhaled.
H372.A	Causes damage to organs through prolonged or repeated exposure if inhaled

Safety Data Sheet dated: 4/16/2015 - version 1

Product code: 2598

Additional classification information





HMIS Health: 3 = SERIOUS

HMIS Health - Is health hazard chronic?: Yes HMIS Flammability: 3 = Flammable liquid

HMIS Reactivity: 0 = MINIMAL HMIS P.P.E.: Safety glasses, gloves

NFPA Health: 3 = SERIOUS

NFPA Flammability: 3 = Flammable liquid

NFPA Reactivity: 0 = MINIMAL NFPA Special Risk: NONE

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

Date 4/16/2015 Production Name ULTRAFLEX LFT WHITE Page n. 7 of 8

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Date 4/16/2015 Production Name ULTRAFLEX LFT WHITE Page n. 8 of 8