



**MATERIAL SAFETY DATA SHEET**  
**FOR COATINGS, RESINS AND RELATED MATERIALS**  
(Approved by U.S. Department of Labor  
"Essentially Similar" to Form OSHA-20)

**NPCA HMIS**

H=1

F=0

R=0

DATE OF PREP: 8-30-00  
PREPARED BY: Howard Burchett, Jr.

**Section I**

MANUFACTURED FOR: Masland Carpet Mills, Inc.  
STREET ADDRESS: 716 Bill Myles Drive  
CITY, STATE, AND ZIP CODE: Saraland, AL 36571  
EMERGENCY PHONE NO: Chemtrec- (800) 424-9300 24hrs. Or (706) 226-0610 days only  
PRODUCT CLASS: Floor Covering Adhesive  
MANUFACTURER'S CODE: Masland 2950  
TRADE NAME: Masland Ultra Premium 2950

**Section II- Hazardous Ingredients**

INGREDIENT	NTP/IARC/ OSHA CARC	PERCENT	TLV PPM	LEL mg/M <sup>3</sup>	VAPOR PRESSURE
------------	------------------------	---------	------------	--------------------------	-------------------

NONE

**Section III – PHYSICAL DATA**

BOILING RANGE: >212°  
VAPOR DENSITY: Heavier than air  
EVAPORATION RATE: Slower than Ether  
PERCENT VOLATILE BY VOLUME: 18% ± 1  
WEIGHT PER GALLON: 10.6 lbs.

**Section IV – FIRE AND EXPLOSIVE HAZARD DATA**

DOT CATEGORY: Latex (N/A)  
FLASH POINT: >220°F  
LEL: N/A  
EXTINGUISHING MEDIA: Regular foam or CO2 or dry chemical  
UNUSUAL FIRE AND  
EXPLOSIVE HAZARDS: Will burn under conditions of extreme heat. Presents no unusual  
Burning characteristics.  
  
SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus with a full face piece  
operated in pressure demand or other positive pressure mode when  
fighting fires.

---

**Section V-HEALTH HAZARD DATA**

---

THRESHOLD LIMIT VALUE:	OSHA – 500ppm, ACGIH TLV –300ppm.
EFFECTS OF OVEREXPOSURE:	If TLV of the product is exceeded or any component is needed, a NIOSH/NSHA jointly approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other respirators under specified conditions.
EMERGENCY AND FIRST AID PROCEDURES:	If breathed excessive amounts, remove to fresh air. EYES: Flush with large amounts of water, lifting upper & lower lids occasionally, get medical attention. SKIN: Thoroughly wash exposed area with soap & water. Remove and launder contaminated clothing before re-use. INGESTION: If, swallowed, call a physician.

---

**Section VI-REACTIVITY DATA**

---

STABILITY:	Stable
CONDITIONS TO AVOID:	Intense heat and flame, strong oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS:	None
HAZARDOUS POLYMERIZATION:	Will not occur.

---

**Section VII – SPILL OR LEAK PROCEDURES**

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:	Dam material, use chemical absorbent shovel and place in safe container.
WASTE DISPOSAL METHOD:	Landfill in accordance with local, state and federal regulations.

---

**Section VIII – SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION:	Normal none, special closed areas, respirator (NIOSH/NSHA approved)
VENTILATION:	Fresh air, cross ventilation indoors.
PROTECTIVE GLOVES:	Neoprene or nitrile.
EYE PROTECTION:	Safety glasses or goggles.
OTHER PROTECTIVE EQUIPMENT:	As needed or applicable.

---

**Section IX – SPECIAL PRECAUTIONS**

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:	Avoid extreme heat or flame.
OTHER PRECAUTIONS:	Working in closed, dead air spaces.