Printing date 24.04.2015

*

*

Version No. 5

Revision: 24.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
· Trade name: <u>UZIN PE 460 Comp. A</u>
\cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against
· Sector of Use
SU19 Building and construction work SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) For professional use only.
• Product category PC1 Adhesives, sealants
• Application of the substance / the mixture 2 Component Epoxy DPM (Component A)
 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Uzin Ltd. Unit 2, Mitchell Court Central Park, Rugby Warwickshire, CV23 0UY, Telephone +44 (0) 1788 530 080 Fax +44 (0) 1788 536508 Email info@uzin.co.uk
• Further information obtainable from: Product safety department email: msds.info@uzin-utz.com
• 1.4 Emergency telephone number: Medical emergencies: +49 30 30 686 790 Transportation emergencies: +49 621 60 43 333
SECTION 2: Hazards identification
• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 GHS09 environment
GIISOS environment
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
GHS07
Skin Irrit. 2 H315 Causes skin irritation.
<i>Eye Irrit.</i> 2 <i>H319 Causes serious eye irritation.</i>
Skin Sens. 1 H317 May cause an allergic skin reaction.
• Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xi; Irritant
R36/38: Irritating to eyes and skin.
Xi; Sensitising
<i>R43:</i> May cause sensitisation by skin contact. N; Dangerous for the environment
<i>R51/53:</i> Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. (Contd. on page 2)

Version No. 5

Revision: 24.04.2015

Trade name: UZIN PE 460 Comp. A

Printing date 24.04.2015

The product ha	Encerning particular hazards for human and environment: Is to be labelled due to the calculation procedure of the "General Classification guideline f the EU" in the latest valid version.
2.2 Label elem Labelling acco	ents rding to Regulation (EC) No 1272/2008
	classified and labelled according to the CLP regulation.
Hazard pictogr	rams GHS07, GHS09
Signal word W	arning
Hazard-determ	ining components of labelling:
	ct: bisphenol-A-(epichlorhydrin) epoxy resin (with an average molecular weight \leq 700)
•	l diglycidyl ether
	xypropoxy)-2,2-dimethylpropane
Hazard statem	ents
H315 Causes st	kin irritation.
H319 Causes se	erious eye irritation.
	se an allergic skin reaction.
	aquatic life with long lasting effects.
Precautionary	
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	
P302+P352	
	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P	2338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lense
D227 + D212	present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
Additional info	rmation:
EUH205 Conto	uins epoxy constituents. May produce an allergic reaction.

- *PBT:* Not applicable.
- **vPvB**: Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: 2 Component Epoxy DPM (Component A)

· Dangerous	components:
-------------	-------------

CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (with an	50-75%
NLP: 500-033-5	average molecular weight \leq 700)	
<i>Reg.nr.: 01-2119456619-26</i>	🗙 Xi R36/38; 🗙 Xi R43; 🎇 N R51/53	
	♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 16096-31-4	1,6-Hexanediol diglycidyl ether	25-50%
EINECS: 240-260-4	🗙 Xi R36/38; 🗙 Xi R43	
Reg.nr.: 01-2119463471-41		
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	5 - <10%
EINECS: 241-536-7	🗙 Xi R38; 🗙 Xi R43	
	🚯 Skin Irrit. 2, H315; Skin Sens. 1, H317	

• Additional information: For the wording of the listed risk phrases refer to section 16.

(Contd. on page 3)

GB

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

Trade name: UZIN PE 460 Comp. A

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- **4.3** *Indication of any immediate medical attention and special treatment needed Also observe the safety data sheet of component B.*
- <u>SECTION 5: Firefighting measures</u>
- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO_{a} powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Wear suitable protective clothing, gloves and eye/face protection. Immediately remove all soiled and contaminated clothing Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes and skin.
- Wash hands before breaks and at the end of work.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.
- *Protect from humidity and water. Protect from frost.*

(Contd. on page 4)

- GB

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

Trade name: UZIN PE 460 Comp. A

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wear suitable protective clothing, gloves and eye/face protection. Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes and skin.
- Wash hands before breaks and at the end of work.
- · Respiratory protection: Not necessary. Ensure that room is well-ventilated during processing.
- · Protection of hands:



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

• Material of gloves Butyl rubber, BR Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.5 mm • Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

• 9.1 Information on basic physical a • General Information	nd chemical properties	
· General Information · Appearance:		
Form:	Fluid	
Colour:	Yellowish	
Odour:	Weak, characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
· Flash point:	> 100 °C	

(Contd. of page 3)

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

Trade name: UZIN PE 460 Comp. A

	(Contd. of pa	age 4
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	1.1 g/cm ³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic at 20 °C:	400 mPas	
Kinematic:	Not determined.	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

May produce violent reactions with bases and numerous organic substances including alcohols and amines. *Exothermic polymerisation.*

Caution: Epoxy material can become extremely hot and may foam up in the container approx. 15-30 min after mixing. Therefore, mix only in metal containers, then apply immediately. Do not leave unattended after mixing. Remove container with mixed product residues to outdoors to allow to react.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

Irritant gases/vapours

At elevated temperatures hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke or nitric oxids may be evolved.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitisation: Sensitisation possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 6)

GB

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

Trade name: UZIN PE 460 Comp. A

Irritant

(Contd. of page 5)

GB

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish

· Additional ecological information:

- General notes: Do not allow product to reach ground water, water course or sewage system. Toxic for aquatic organisms Also poisonous for fish and plankton in water bodies.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

The product contains materials that are harmful to the environment. Do not allow product to reach ground water, water course or sewage system. Disposal should be in accordance with local, state or national legislation.

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
\cdot 14.2 UN proper shipping name	
· ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Bisphenol-A-epoxy resin (averag molecular weight ≤700))
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Bisphenol-A-epoxy resin (averag molecular weight ≤700)), MARINE POLLUTANT
·IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Bisphenol-A-epoxy resin (averag molecular weight ≤ 700))

Safety data sheet

according to 1907/2006/EC, Article 31 Printing date 24.04.2015 Version No. 5 Revision: 24.04.2015 Trade name: UZIN PE 460 Comp. A (Contd. of page 6) · 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 9 Miscellaneous dangerous substances and articles. · Label 9 · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: Yes Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · Special marking (IATA): · 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. 90 · Danger code (Kemler): F-A, S-F· EMS Number: · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · ADR \cdot Limited quantities (LQ) 5L· Transport category 3 · Tunnel restriction code Ε UN3082, ENVIRONMENTALLY HAZARDOUS · UN "Model Regulation": SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-epoxy resin (average molecular weight \leq 700)), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 8)

GB

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

(Contd. of page 7)

GB

Trade name: UZIN PE 460 Comp. A

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Recommended restriction of use For professional use only.

· Department issuing MSDS: Product safety department

· Contact:

Dr. M. Zieger, phone +49 (0)731 4097 207 *E-Mail: msds.info@uzin-utz.com*

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

• * Data compared to the previous version altered.

Printing date 24.04.2015

*

*

Version No. 5

Revision: 24.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
· Trade name: <u>UZIN PE 460 Comp. B</u>
· 1.2 Relevant identified uses of the substance or mixture and uses advised against
· Sector of Use
SU19 Building and construction work SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) For professional use only.
• Product category PC1 Adhesives, sealants
• Application of the substance / the mixture 2 Component Epoxy DPM (Component B)
 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Uzin Ltd. Unit 2, Mitchell Court Central Park, Rugby Warwickshire, CV23 0UY, Telephone +44 (0) 1788 530 080 Fax +44 (0) 1788 536508 Email info@uzin.co.uk Further information obtainable from:
Product safety department email: msds.info@uzin-utz.com
• 1.4 Emergency telephone number: Medical emergencies: +49 30 30 686 790 Transportation emergencies: +49 621 60 43 333
SECTION 2: Hazards identification
• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 GHS05 corrosion
Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
GHS09 environment
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. GHS07
Skin Sens. 1 H317 May cause an allergic skin reaction.
· <u>Class</u> ification according to Directive 67/548/EEC or Directive 1999/45/EC
C; Corrosive
R34: Causes burns.
Xi; Sensitising
<i>R43:</i> May cause sensitisation by skin contact.
(Contd. on page 2

Version No. 5

Revision: 24.04.2015

Trade name: UZIN PE 460 Comp. B

Printing date 24.04.2015

	(Contd. of page 1
N; Danger	ous for the environment
R51/53: Toxic	to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
The product has	acerning particular hazards for human and environment: to be labelled due to the calculation procedure of the "General Classification guideline for the EU" in the latest valid version.
The product is cl	ding to Regulation (EC) No 1272/2008 lassified and labelled according to the CLP regulation. ms GHS05, GHS07, GHS09
Alkylated poly-a. m-Phenylene bis Hazard statemen H314 Causes sev H317 May cause	(methylamine), reaction products
Precautionary st	
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P303+P361+P3	53 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333+P313 P305+P351+P3	If skin irritation or rash occurs: Get medical advice/attention. 38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i
1 303 +1 331 +1 3	present and easy to do. Continue rinsing.
P310	present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
	present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If eye irritation persists: Get medical advice/attention.

· vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: 2 Component Epoxy DPM (Component B)

· Dangerous components:	
Alkylated poly-aza-alkanes	75-100%
🛃 C R34; 🗙 Xi R43	
🔗 Skin Corr. 1B, H314; 🚸 Skin Sens. 1, H317	-
m-Phenylene bis(methylamine), reaction products	5 - <10%
🛃 C R35; 🗙 Xn R22-48/22; 💓 Xi R43; 🌇 N R50/53	
STOT RE 2. H373: Skin Corr. 1A. H314: Aquatic Acute 1. H400: Aquatic Chronic 1.	1
H410; (Acute Tox. 4, H302; Skin Sens. 1, H317	
×	

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

(Contd. of page 2)

Trade name: UZIN PE 460 Comp. B

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Wear suitable protective clothing, gloves and eye/face protection. Immediately remove all soiled and contaminated clothing Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes and skin. Wash hands before breaks and at the end of work.

· Information about fire - and explosion protection: No special measures required.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Protect from frost.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

Trade name: UZIN PE 460 Comp. B

	(Contd. of page
8.1 Control parameters	
	that require monitoring at the workplace:
	in any relevant quantities of materials with critical values that have to b
monitored at the workplace.	
8.2 Exposure controls	
Personal protective equipment	nt:
General protective and hygier	
Immediately remove all soiled	
	ing, gloves and eye/face protection.
Keep away from foodstuffs, be	
Avoid contact with the eyes ar	
Wash hands before breaks and	
	ecessary. Ensure that room is well-ventilated during processing.
Protection of hands:	ceessary. Ensure that toom is well vehillated during processing.
Trotection of numus.	
ı M	
Use gloves of stabl	e material (e.g. Nitrile) - if necessary tricoted to improve the wearability.
Material of gloves	
Butyl rubber, BR	
Nitrile rubber, NBR	
Recommended thickness of the	
Penetration time of glove man	terial
The exact break trough time	has to be found out by the manufacturer of the protective gloves and has to l
observed.	
Eye protection:	
Tightly sealed gog	gles
SECTION 9: Physical a	nd chamical properties
SECTION 9: Physical a	na chemical properties
9.1 Information on basic phy	sical and chemical properties
General Information	sicu una chemicai properties
Appearance:	
Form:	Fluid
Form: Colour:	Yellowish
Odour:	Fish-like Not determined
Odour threshold:	Not determined.
pH-value at 20 °C:	11

· pH-value at 20 °C:	11
• Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.
· Flash point:	> 100 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
	(Contid on page

(Contd. on page 5) GB

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

Trade name: UZIN PE 460 Comp. B

		(Contd. of page 4
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	1.03 g/cm ³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic at 20 °C:	500 mPas	
Kinematic:	Not determined.	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions
- Strong exothermic reaction with acids.

Caution: Epoxy material can become extremely hot and may foam up in the container approx. 15-30 min after mixing. Therefore, mix only in metal containers, then apply immediately. Do not leave unattended after mixing. Remove container with mixed product residues to outdoors to allow to react.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:
- Corrosive gases/vapours

At elevated temperatures hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke or nitric oxids may be evolved.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

- Primary irritant effect:
- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitisation: Sensitisation possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Corrosive

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 6)

GB

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

(Contd. of page 5)

Trade name: UZIN PE 460 Comp. B

- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:
- Do not allow product to reach ground water, water course or sewage system. Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

· 12.5 Results of PBT and vPvB assessment

- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

The product contains materials that are harmful to the environment. Do not allow product to reach ground water, water course or sewage system. Disposal should be in accordance with local, state or national legislation.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· 14.1 UN-Number · ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name · ADR	2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S (Alkylated poly-aza-alkanes), ENVIRONMENTALLY HAZARDOUS
· IMDG · IATA	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Alkylated poly-aza-alkanes), MARINE POLLUTANT POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Alkylated poly-aza-alkanes)
· 14.3 Transport hazard class(es)	[···]
I I I I I I I I I I I I I I I I I I I	
· Class	8 Corrosive substances.
· Class · Label	8 Corrosive substances. 8
· Label	

Trade name: UZIN PE 460 Comp. B		
Printing date 24.04.2015	Version No. 5	Revision: 24.04.2015
	5	

	(Contd. of page	
· Label	8	
· 14.4 Packing group		
· ADR, IMDĞ, IATA	П	
· 14.5 Environmental hazards:		
· Marine pollutant:	Yes	
	Symbol (fish and tree)	
· Special marking (ADR):	Symbol (fish and tree)	
· 14.6 Special precautions for user	Warning: Corrosive substances.	
· Danger code (Kemler):	80	
· EMS Number:	F- A , S - B	
· 14.7 Transport in bulk according to Anne	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· Transport/Additional information:		
$\cdot ADR$		
· Limited quantities (LQ)	1L	
· Tunnel restriction code	E	
· UN "Model Regulation":	UN2735, POLYAMINES, LIQUID, CORROSIVE, N.O.S (Alkylated poly-aza-alkanes), ENVIRONMENTALL HAZARDOUS, 8, II	

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- R22 Harmful if swallowed.
- R34 Causes burns.
- R35 Causes severe burns.
- *R43 May cause sensitisation by skin contact.*
- R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Recommended restriction of use For professional use only.

· Department issuing MSDS: Product safety department

· Contact:

Dr. M. Zieger, phone +49 (0)731 4097 207 E-Mail: msds.info@uzin-utz.com

(Contd. on page 8)

GB

Printing date 24.04.2015

Version No. 5

Revision: 24.04.2015

(Contd. of page 7)

Trade name: UZIN PE 460 Comp. B

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 \cdot * Data compared to the previous version altered. GB