

## Section 1: IDENTIFICATION

#### **1.1 PRODUCT IDENTIFIER**

- Product Name: Crack Buster® Pro Crack Prevention Mat Underlayment
- Product Code: Not Available
- **1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE** 
  - Product Use: Underlayment

#### **1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS**

- Name/Address: Custom Building Products 3490 Piedmont Road, Suite 1300 Atlanta, GA 30329
- **Telephone Number:** (562)-598-8808

#### **1.4 EMERGENCY TELEPHONE NUMBER**

Emergency Telephone	INFOTRAC 1-800-535-5053 (US and Canada)
Number:	INTERNATIONAL + 1-352-323-3500

### Section 2: HAZARD(S) IDENTIFICATION

#### 2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR

#### 1910.1200 (OSHA HAZCOM2012)

Skin Irritation	Category 2
Eye Irritation	Category 2B
Skin sensitization	Category 1
Carcinogenicity	Category 1A

#### 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

- 2.2a SIGNAL WORD: WARNING!
- 2.2b HAZARD STATEMENTS Causes skin irritation Causes eye irritation May cause an allergic skin reaction

May cause cancer



#### 2.2c HAZARD PICTOGRAMS



### 2.2d PRECAUTIONARY STATEMENTS

i.	PREVENTION	Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/ vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.
ii.	RESPONSE	If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: call a poison center/doctor. If exposed or concerned: get medical advice/attention
iii.	STORAGE	Store in a well-ventilated place.
iv.	DISPOSAL	Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.

#### 2.3 ADDITIONAL INFORMATION

#### 2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED Not applicable

- **2.3b** UNKNOWN ACUTE TOXICITY 85% of the mixture consists of ingredient(s) of unknown acute toxicity.
- 2.3c WHMIS CLASSIFICATION Class D2B – Skin/Eye Irritant Class D2A - Carcinogenicity

### 2.3d LABEL ELEMENTS ACCORDING TO WHMIS

#### i. WHMIS HAZARD SYMBOLS



ii. SIGNAL WORD



WARNING!

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### **3.1 MIXTURES**

Chemical Name	CAS Number	Weight %
Asphalt	8052-42-4	60 – 100%*
Hydrous magnesium silicate	14807-96-6	10 – 30%*
Calcium Carbonate	471-34-1	10 – 30%*
1,3-Butadiene/styrene copolymers	9003-55-8	10 – 30%*

\*The exact percentage (concentration) of composition has been withheld due to a batch-to-batch variability in accordance with paragraph (ii) of §1910.1200.

# Section 4: FIRST-AID MEASURES

#### 4.1 DESCRIPTION OF THE FIRST-AID MEASURES

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
Skin Contact:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
Inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
Ingestion:	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

#### 4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	Causes eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Skin Contact:	Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact.



Inhalation:

May cause respiratory tract irritation.

Ingestion:

May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

### 4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Not applicable

## Section 5: FIRE-FIGHTING MEASURES

#### 5.1 FLAMMABILITY

Flammability: Not Flammable by WHMIS/OSHA HAZCOM2012 Criteria

#### **5.2 EXTINGUISHING MEDIA**

- **5.2a.** Suitable Extinguishing Media: Treat for surrounding material.
- 5.2b. Unsuitable Extinguishing Media: Not available.

#### 5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

**5.3a. Products of Combustion:** May include, and are not limited to: oxides of carbon

#### 5.3b. Explosion Data

- i. Sensitivity to Mechanical Impact: Not available.
- ii. Sensitivity to Static Discharge: Not available.

# Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment:	Recover all usable material. Use appropriate Personal Protective Equipment (PPE).
Methods for Cleaning-Up:	Vacuum or sweep material and place in a disposal container. Dispose of unwanted material properly in accordance with all local,



regional, national and international regulations.

## Section 7: HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

Handling:Use in well-ventilated areas. Wear chemical resistant gloves and<br/>eye protection. Do not mix with other chemical products, except as<br/>indicated by the manufacturers. Do not get in eyes. Do not get on<br/>skin or clothing. Do not take internally.

**General Hygiene Advice:** Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

#### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage:Keep out of the reach of children. Keep container tightly closed.<br/>Store at room temperature and keep containers closed when not in<br/>use. Avoid any dust buildup by frequent cleaning and suitable<br/>construction of the storage area. Keep dry until use.

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 CONTROL PARAMETER Exposure Guidelines

Occupational Exposure Limits		
Chemical Name	OSHA-PEL	ACGIH-TLV
Asphalt	5 mg/m³	0.5 mg/m³
Hydrous magnesium silicate	2 mg/m³	2 mg/m³
Calcium Carbonate	5 mg/m³ (Resp.)	5 mg/m³
	15 mg/m <sup>3</sup> (Total)	_
1,3-Butadiene/styrene copolymers	Not available	Not available

#### **8.2 EXPOSURE CONTROLS**

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

#### 8.3 INDIVIDUAL PROTECTION MEASURES

#### 8.3a. Personal Protective Equipment:

i. **Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]



- ii. Skin Protection:
  - 1. Hand Protection: Wear chemical resistant gloves.
  - 2. Body Protection: Wear suitable protective clothing
- iii. Respiratory Protection: A NIOSH approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.

Appearance (physical state, color, etc.):	sheet like material, in rolls (solid)
Odor:	Possible slight odor
Odor Threshold:	Not available
pH:	Not available
Melting point/Freezing point:	Not available
Initial boiling point and boiling range:	Not available
Flash point:	> 525°F
Evaporation rate (Water=1):	Not available
Flammability:	Not flammable
Upper Flammability/Explosive Limit:	Not available
Lower Flammability/Explosive Limit:	Not available
Vapor Pressure	Not available
Vapor Density:	Not available
Relative Density:	1 – 1.3 g/cc
Solubility in Water:	Not available
Partition coefficient: n-octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition Temperature:	Not available
Viscosity (cps):	Not available
VOC Content:	0 g/L (0%)

#### Section 9: PHYSICAL AND CHEMICAL PROPERTIES

# Section 10: STABILITY AND REACTIVITY

#### 10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

#### **10.2. CHEMICAL STABILITY**

Stable under normal storage conditions. Keep dry in storage.

Page 6 of 12



#### **10.3. POSSIBILITY OF HAZARDOUS REACTION**

No dangerous reaction known under conditions of normal use.

#### **10.4. CONDITIONS TO AVOID**

Heat. Incompatible materials.

#### 10.5. INCOMPATIBLE MATERIALS Not Available

#### 10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon.

### Section 11: TOXICOLOGICAL INFORMATION

#### 11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

#### 11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

Eye Contact:	Causes eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Skin Contact:	Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact.
Inhalation:	May cause respiratory tract irritation.
Ingestion:	May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

Acute Toxicity		
Chemical Name	LC50	LD50
Asphalt	Not available	Not available
Hydrous magnesium silicate	Not available	Not available
Calcium Carbonate	Not available	Oral: 6450 mg/kg, rat
1,3-Butadiene/styrene copolymers	Not available	Not available

Carcinogenicity		
Chemical Name	Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65)	
Asphalt	Not Listed	
Hydrous magnesium silicate	I-3, CP65	
Calcium Carbonate	Not Listed	
1,3-Butadiene/styrene copolymers	Not Listed	

Page 7 of 12



### 11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

SHORT-TERM		
Skin Corrosion/Irritation:	Causes skin irritation	
Serious Eye Damage/Irritation: Causes eye irritation		
Respiratory Sensitization:	Not available	
Skin Sensitization:	May cause an allergic skin reaction	
STOT-Single Exposure:	Not available	
Aspiration Hazard:	Not available	
LONG-TERM		
Carcinogenicity:	May cause cancer	
Germ Cell Mutagenicity:	Not available	
Reproductive Toxicity:	Not available	
STOT-Repeated Exposure:	Not available	
Synergistic/Antagonistic Effects:	Not available	

### Section 12: ECOLOGICAL INFORMATION

### 12.1. ECOTOXICITY

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

Ecotoxicity			
Chemical Name	EC50/NOEC-48 Hours	LC50/NOEC-96 Hours	
Asphalt	Not available	Not available	
Hydrous magnesium silicate	Not available	Not available	
Calcium Carbonate	Not available	Not available	
1,3-Butadiene/styrene copolymers	Not available	Not available	

# 12.2. PERSISTENCE AND DEGRADABILITY

Not available

- 12.3. BIOACCUMULATIVE POTENTIAL Not available
- 12.4. MOBILITY IN SOIL

Not available

12.5. OTHER ADVERSE EFFECTS Not available



# Section 13: DISPOSAL CONSIDERATIONS

#### 13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

#### **13.2. OTHER DISPOSAL CONSIDERATIONS**

Not available

## Section 14: TRANSPORT INFORMATION

DOT (U.S.)	TDG (CANADA)	
UN NUMBER:	UN NUMBER:	
Not regulated	Not regulated	
UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:	
Not regulated	Not regulated	
TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):	
Not regulated	Not regulated	
PACKING GROUP (if applicable):	PACKING GROUP (if applicable):	
Not regulated	Not regulated	

SUMMARY: Product is not regulated under DOT/TDG and other transportation regulations.

#### 14.1. ENVIRONMENTAL HAZARDS

Not available

**14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE** Not available

#### 14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

## Section 15: REGULATORY INFORMATION

#### 15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

**US:** SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Page 9 of 12



#### **15.2. US FEDERAL INFORMATION:**

	SARA TITLE III			
CHEMICAL NAME	SECTION 302	SECTION 304	CERCLA RQ	SECTION 313
	(EHS) TPQ (LBS)	EHS RQ (LBS)	(LBS)	(TRI)
Asphalt	Not Listed	Not Listed	Not Listed	Not Listed
Hydrous magnesium silicate	Not Listed	Not Listed	Not Listed	Not Listed
Calcium Carbonate	Not Listed	Not Listed	Not Listed	Not Listed
1,3-Butadiene/styrene copolymers	Not Listed	Not Listed	Not Listed	Not Listed

### 15.3. US STATE RIGHT TO KNOW LAWS:

California Proposition 65:	<b>WARNING!</b> This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm
Other U.S. States "Right to Know" Lists:	
New Jersey:	Asphalt: <b>CAS#8052-42-4</b> Hydrous Magnesium Silicate: <b>CAS#14807-96-6</b> Calcium carbonate: <b>CAS#471-34-1</b> 1,3-Butadiene/styrene copolymers: <b>CAS#14807-96-6</b>
Pennsylvania:	Asphalt: CAS#8052-42-4 Hydrous Magnesium Silicate: CAS#14807-96-6 Calcium carbonate: CAS#471-34-1 1,3-Butadiene/styrene copolymers: CAS#14807-96-6
Massachusetts:	Asphalt: <b>CAS#8052-42-4</b> Hydrous Magnesium Silicate: <b>CAS#14807-96-6</b> Calcium carbonate: <b>CAS#471-34-1</b> 1,3-Butadiene/styrene copolymers: <b>CAS#14807-96-6</b>
Minnesota:	Asphalt: <b>CAS#8052-42-4</b> Hydrous Magnesium Silicate: <b>CAS#14807-96-6</b> Calcium carbonate: <b>CAS#471-34-1</b> 1,3-Butadiene/styrene copolymers: <b>CAS#14807-96-6</b>
Florida:	Not Available
Michigan:	Not Available

### **15.4. GLOBAL INVENTORIES**

Chemical Name	USA TSCA	Canada DSL/NDSL
Asphalt	Yes	DSL
Hydrous magnesium silicate	Yes	DSL
Calcium Carbonate	Yes	DSL(*)
1,3-Butadiene/styrene copolymers	Yes	DSL

\*Exemption: Natural occurring chemical



### 15.5. NFPA AND HMIS RATINGS:





HMIS

Hazard Index		
4	Severe Hazard	
3	Serious Hazard	
2	Moderate Hazard	
1	Slight Hazard	

1	HEALTH	PROTECTIVE EQUIPMENT INDEX	
		A	G 승+\$+ 🏤
0	FLAMMABILITY	B ⇔+\$	H 🖘 + 🕯 + 🛔 + 🦣
0	REACTIVITY		
•	PERSONAL	C ↔+\$+≛	◧⇔+ঙ+♠
U	PROTECTION	D 🖯+🗲 🞽	J 🖘+🖇+ 🛓+ 🙀
в		<b>E⇔+\$+</b> ♠	K 😪 + 🛠 + 👫 + 🖿
		E C. St. B.	Ask your supervisor for special handling instructions



#### 15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65	California Proposition 65		
OSHA (O)	Occupational Safety and Health Administration		
ACGIH (G)	American Conference of Governmental Industrial Hygienists		
	A1 – Confirmed human carcinogen		
	A2 – Suspected human carcinogen		
	A3 – Animal carcinogen		
	A4 – Not classifiable as a human carcinogen		
	A5 – Not suspected a human carcinogen		
IARC (I)	International Agency for Research on Cancer		
	<ul> <li>1 – The agent (mixture) is carcinogenic to humans</li> </ul>		
	<ul> <li>2A – The agent (mixture) is probably carcinogenic to humans; there</li> </ul>		
	is limited evidence of carcinogenicity in humans and sufficient		
	evidence of carcinogenicity in experimental animals.		
	<ul> <li>2B – The agent (mixture) is possibly carcinogenic to humans; there</li> </ul>		
	is limited evidence of carcinogenicity in humans in the absence of		
	sufficient evidence of carcinogenicity in experimental animals.		
	• 3 – The agent (mixture, exposure circumstance) is not classifiable		
	as to its carcinogenicity to humans.		
	<ul> <li>4 – The agent (mixture, exposure circumstance) is probably not</li> </ul>		
	carcinogenic to humans.		
NTP (N)	National Toxicology Program		
	<ul> <li>1 – Known to be carcinogens</li> </ul>		
	<ul> <li>2 – Reasonably anticipated to be carcinogens</li> </ul>		

### **Section 16: OTHER INFORMATION**

Date of Preparation:	October 13, 2014
Version:	2.0
Revision Date:	N/A

**Disclaimer:** We believe the statements, technical information and recommendations contained are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by:

Custom Building Products Phone: (562)-968-2980 www.custombuildingproducts.com

# **End of Safety Data Sheet**