SAFETY DATA SHEET

1. Identification

Product identifier USG DUROCK Brand X2 Primer-Sealer

Other means of identification

SDS number 14000020007 **Synonyms** Primer, Sealer Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street

Chicago, Illinois 60661-3637

1-800-874-4968 **Telephone** Website www.usg.com **Emergency phone number** 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction.

Precautionary statement

Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the Prevention

workplace. Wear protective gloves.

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Response

Wash contaminated clothing before reuse.

Store as indicated in Section 7. Storage

Disposal Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Propylene glycol	57-55-6	< 5

Composition comments All concentrations are in percent by volume unless otherwise indicated.

4. First-aid measures

Inhalation Exposure to mists may cause temporary irritation to eyes, skin, nose, throat, and upper respiratory

tract. Move injured person into fresh air and keep person calm under observation. Get medical

attention if symptoms persist.

Skin contact Rinse area with plenty of water. Get medical attention if irritation develops and persists.

Do not rub eyes. Flush thoroughly with water. If burning, redness, itching, pain, or other symptoms Eye contact

develop or persist get medical attention.

USG DUROCK Brand X2 Primer-Sealer SDS US 1/6 **Ingestion** Rinse mouth. Get medical attention if any discomfort occurs.

Most important

symptoms/effects, acute and

delayed

Indication of immediate Provide general medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials. Not applicable.

Unsuitable extinguishing

media

Not applicable

Specific hazards arising from

the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Under normal conditions of intended use, this product is not expected to be a health risk.

Specific methodsCool material exposed to heat with water spray and remove it if no risk is involved.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Prevent entry into confined areas or water systems. Dilute with water and mop or wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Dispose of waste according to local regulations.

Environmental precautions A

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Minimize exposure to mists. In case of insufficient ventilation, wear suitable respiratory equipment.

Observe good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities

Store material between 18°C(65°F) and 35°C(95°F). Store in a cool (frost-free), dry and well ventilated location. Do not allow material to freeze. Store in a closed container away from incompatible materials, food, or drinking water. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep

containers closed when not in use.

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	Form	
Propylene glycol (CAS	TWA	10 mg/m3	Aerosol.	
57-55-6)				

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines No exposure standards allocated.

Appropriate engineering Provide sufficient ventilation for operations causing mist formation. Observe occupational exposure

controls limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

Hand protection It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

921457 Version #: 01 Revision date: - Issue date: 10-November-2014

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator

Thermal hazards None.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Aqueous polymer. Orange tint. Color Mild. Odor

Odor threshold Not applicable.

5 - 7

Melting point/freezing point Not applicable. Initial boiling point and boiling

range

212 °F (100 °C)

Not applicable. Flash point **Evaporation rate** Not applicable. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not applicable.

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%) Not applicable. Explosive limit - upper (%) Not applicable. Not applicable. Vapor pressure Not applicable.

Vapor density Relative density 1 (H2O=1)

Solubility(ies)

Insoluble. Solubility (water)

Partition coefficient

Decomposition temperature

Not applicable.

(n-octanol/water) **Auto-ignition temperature**

Not applicable. Not applicable. Not applicable.

Other information

Viscosity

8.3 lb/ft3 **Bulk density** VOC (Weight %) Not applicable.

10. Stability and reactivity

USG DUROCK Brand X2 Primer-Sealer

Reactivity The product is stable and non reactive under normal conditions of storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

921457 Version #: 01 Revision date: -Issue date: 10-November-2014 **Hazardous decomposition**

products

None known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Spray mist may irritate the respiratory system.

Skin contact Prolonged or repeated skin contact may cause irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure may cause temporary irritation, redness, or discomfort.

Information on toxicological effects

Acute toxicity Low hazard for usual industrial or commercial handling by trained personnel.

Components Species Test Results

Propylene glycol (CAS 57-55-6)

Acute Oral

LD50 Rat 30 g/kg

Skin corrosion/irritation Prolonged or repeated skin contact may cause irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction after a single exposure or with repeated or prolonged skin

contact.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

No data available, but none expected.

Specific target organ toxicity -

repeated exposure

No data available, but none expected.

Aspiration hazard No data available.

Chronic effects May cause allergic skin disorders in sensitive individuals.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Bioaccumulation is not expected.

Partition coefficient n-octanol / water (log Kow)

Propylene glycol (CAS 57-55-6) -0.92

Mobility in soilNot available.Other adverse effectsNone expected.

13. Disposal considerations

Disposal instructionsDispose waste and residues in accordance with applicable federal, state, and local regulations.

Avoid discharge into water courses or onto the ground.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

USG DUROCK Brand X2 Primer-Sealer SDS US

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging

Since emptied containers retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

This substance/mixture is not intended to be transported in bulk.

Allica II of Marti

the IBC Code

15. Regulatory information

US federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Yes

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Propylene glycol (CAS 57-55-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Propylene glycol (CAS 57-55-6)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

USG DUROCK Brand X2 Primer-Sealer

SDS US

country(s).

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date 10-November-2014

Revision date - Version # 01

Further information NFPA Ratings:

Health: 1 Flammability: 0 Physical hazard: 0

NFPA Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



List of abbreviations

NFPA: National Fire Protection Association.

Disclaimer This information is provided without warranty. The information is believed to be correct. This

information should be used to make an independent determination of the methods to safeguard

workers and the environment.

USG DUROCK Brand X2 Primer-Sealer