SAFETY DATA SHEET

	SECTION 1 – IDENTIFICATION
Product Identifier Product ID Number Chemical Family Trade Name/Synonyms Material Use Uses Advised Against Manufacturer's name and addres	 ARDEX MC[™] PLUS PRIMER Resin (Part A) 70013731 Mixture ARDEX MC PLUS PRIMER Resin Primer in Two-Coat Moisture Control System for Concrete No information available. Supplier's name and address:
(ARDEX)	Refer to Manufacturer
ARDEX Engineered Cement 400 Ardex Park Dr. Aliquippa, PA 15001 USA	S
Information Telephone No. Website Address 24 Hr Emergency Telephone #	: (724) 203-5000 : <u>http://www.ardexamericas.com</u> : CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)
SE	CTION 2 – HAZARDS IDENTIFICATION
GHS Classification per 29 CFR 1	910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)
	: Skin Sensitizer Category 1 Eye Irritant Category 2A Skin Irritant Category 2
GHS Pictograms	
GHS Pictograms Signal Word	: Varning
Signal Word	: Warning Causes serious eye irritation. May cause an allergic skin reaction. Causes skin irritation.
-	: Causes serious eye irritation. May cause an allergic skin reaction.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	% (by weight)
25068-38-6	30 - 60
55492-52-9	10 – 30
1317-65-3	10 – 30
68609-97-2	5 – 10
14808-60-7	0.1-1
	25068-38-6 55492-52-9 1317-65-3 68609-97-2

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

	SECTION 4 – FIRST AID MEASURES
General	: Call a Poison Center or doctor if you feel unwell.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: call a doctor/physician.
Skin contact	: Remove/Take off immediately all contaminated clothing. Flush affected skin with gently flowing lukewarm water for at least 20 minutes. Seek immediate medical attention/advice.
Eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
Ingestion	 Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.
Notes for Physician	: Treat symptomatically.
Signs and symptoms of short-t	erm (acute) exposure
Inhalation	: Inhalation of vapors may cause mild irritation of the respiratory system. Symptoms may include coughing and shortness of breath.
Skin	 Causes irritation. Symptoms may include redness and itching. Prolonged or repeated skin contact may cause an allergic skin reaction.
Eyes	: Causes irritation. Symptoms may include redness, itching or pain.
Ingestion	: May cause stomach pain with nausea and vomiting.
Effects of long-term (chronic) e	exposure
	 Prolonged inhalation may cause adverse lung effects with symptoms including coughing and shortness of breath. Some individuals may experience a sensitization reaction of the skin after an initial exposure. Subsequent exposures may cause a hypersensitive skin reaction (rash, swelling).
Indication of need for immediate	medical attention or special treatment
	: Difficulty breathing persists after removing the person to fresh air.
	Any exposure to the eye which causes irritation.
	Chemical burns to the skin. Blue color of the skin (cyanotic) after exposure.
	Ingestion.
S	ECTION 5 – FIRE FIGHTING MEASURES
Suitable extinguishing media Unsuitable extinguishing media	: Use extinguishing media appropriate for surrounding materials.: None known.

ishing media	: None known.
--------------	---------------

Hazardous combustion products : Carbon oxides and/or low molecular weight hydrocarbons.

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.

Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)

: Not flammable

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear chemically resistant personal protective equipment during cleanup. Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment. Protective equipment : Refer to Section 8 on this Safety Data Sheet, EXPOSURE CONTROLS / PERSONAL PROTECTION, for additional information on acceptable personal protective equipment. Emergency procedures : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002). US CERCLA Reportable quantity (RQ): None reported. Spill response / clean-up : Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal Notify the appropriate authorities as required. Environmental precautions : Do not allow product to enter waterways. Do not allow material to contaminate ground water system. Disposal of spilled material : See Section 13.		SECTION 7 – HANDLING AND STORAGE
access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.Protective equipment: Refer to Section 8 on this Safety Data Sheet, EXPOSURE CONTROLS / PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.Emergency procedures:If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002). US CERCLA Reportable quantity (RQ): None reported.Spill response / clean-up:Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal Notify the appropriate authorities as required.:Environmental precautions:Do not allow product to enter waterways. Do not allow material to contaminate	Disposal of spilled material	: See Section 13.
access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment. Protective equipment : Refer to Section 8 on this Safety Data Sheet, EXPOSURE CONTROLS / PERSONAL PROTECTION, for additional information on acceptable personal protective equipment. Emergency procedures : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002). US CERCLA Reportable quantity (RQ): None reported. : Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later	Environmental precautions	
Protective equipment access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment. Protective equipment : Refer to Section 8 on this Safety Data Sheet, EXPOSURE CONTROLS / PERSONAL PROTECTION, for additional information on acceptable personal protective equipment. Emergency procedures : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).	Spill response / clean-up	product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later
Protective equipment access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment. Protective equipment : Refer to Section 8 on this Safety Data Sheet, EXPOSURE CONTROLS / PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.	Emergency procedures .	environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).
access to area until completion of clean-up. All persons dealing with clean-up		PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.
	Personal precautions	access to area until completion of clean-up. All persons dealing with clean-up

Safe handling procedures	Observe good hygiene standards. Do not eat, drink or smoke in the work area. Wash thoroughly after handling. Avoid contact with skin and eyes. Avoid repeated or prolonged skin contact. Avoid breathing vapors or mists of this product. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed. Use only with adequate ventilation.
Storage requirements	Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Avoid storing in direct sunlight. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.
•	Strong oxidizing agents.
Special packaging materials	Always keep in containers made of the same materials as the supply container.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure limits

: No exposure limits have been established for the product. Below are exposure limits for the ingredients in the product.

Ingredients	CAS #	ACGIH 1	ΓLV	OSHA P	EL
		TWA	STEL	PEL	STEL
2,2-bis(4-hydroxyphenyl)propane, polymer with (chloromethyl)oxirane	25068-38-6	N/Av	N/Av	N/Av	N/Av
Phenol, 2,2'-methylenebis-, polymer with (chloromethyl)oxirane	55492-52-9	N/Av	N/Av	N/Av	N/Av
Alkyl (C12-14) glycidyl ether	68609-97-2	N/Av	N/Av	N/Av	N/Av
Calcium Carbonate (Limestone)	1317-65-3	TLV Withdrawn In 2007	N/Av	15 mg/m ³ (Total dust); 5 mg/m ³ (respirable)	N/Av
Crystalline Silica, Quartz	14808-60-7	0.025 mg/m ³ (respirable fraction)	N/Av	0.1 mg/m ³ (respirable) (final rule limit)	N/Av

Engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product.

Eye / face protection

: Chemical goggles must be worn when using this product. A face shield is recommended if splashing is possible.

ARDEX MC[™] PLUS PRIMER RESIN (Part A) Two-Coat Moisture Control System for Concrete 06-Mar-2015

Skin protection	Wear chemical resistant protective clothing and impervious gloves. Materia as nitrile rubber or Viton (fluorocarbon rubber) are recommended.	ials such
Body protection	Where extensive exposure to product is possible, use resistant coveralls, boots to prevent contact.	apron and
Respiratory protection	If work process generates excessive quantities of vapor or dust, or expose excess of any PEL, wear an appropriate organic vapor respirator.	ures in
Site safety equipment	An eyewash station and safety shower should be made available in the in working area.	nmediate
General hygiene precautions	Avoid contact with eyes, skin and clothing. Do not breathe vapors/dust. I eat, drink or smoke when using this product. Clean all equipment and clot end of each work shift.	

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Liquid	Appearance	:	Red liquid
Odor	:	Characteristic	Odor threshold	:	N/Av
рН	:	N/Av	Specific gravity	:	1.22
Boiling point	:	>392°F (>200°C)	Coefficient of water/oil distribution	:	N/Av
Melting/Freezing point	:	N/Av	Solubility in water	:	Immiscible
Vapor pressure (mm Hg @ 20°C / 68°F)	:	N/Av	Evaporation rate (n-Butyl acetate = 1)	:	N/Av
Vapor density (Air = 1)	:	N/Av	Volatiles (% by weight)	:	N/Av
Volatile organic compounds (VOCs)	:	30 g/L A+B, ASTM	1 D2369		
Decomposition temperature	:	N/Av	Flammable Classification	:	Not Flammable
Flash point	:	>212°F (100°C)	Lower flammable limit (% by vol)	:	Not available
Flash point method	:	Setaflash closed	Upper flammable limit (% by vol)	:	Not available
Auto-ignition temperature	:	Not available	Oxidizing properties	:	None
Flame projection length	:	Not available	Flashback observed	:	Not available
Explosion data: Sensitivity to mec	ha	nical impact / sta	atic discharge		

Explosion data: Sensitivity to mechanical impact / static discharge

Viscosity

: Not available

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

Reactivity	Product reacts with amines to form polymers. Heat is evolved by this reaction.
Stability and reactivity :	Stable under the recommended storage and handling conditions prescribed.
Hazardous polymerization :	Hazardous polymerization does not occur.
Conditions to avoid :	Avoid prolonged exposure to heat.
Materials to avoid and incompatability	
:	Oxidizing agents.
Lleserdeus deservessition products	

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

: Not expected to be sensitive to mechanical impact or static discharge.

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of Exposure	: Inhalation: YES	Skin Absorption: NO	Skin and Eyes:	Yes Ingestion: YES
Signs and symptoms of short-terr	n (acute) exposure			
	: See Section 4.			
Signs and symptoms of long-term	ı (chronic) exposure			
	: See Section 4.			
Calculated Acute Toxicity Estimat	es for the Product			
Inhalation	: Not Available			
Oral	: > 8000 mg/kg			
Dermal	: > 5000 mg/kg			

Page 5 of 7

	LC50 (4 hr)	LC	050
Ingredients	Inhalation, rat	Oral, rat	Dermal, rabbit
2,2-bis(4- hydroxyphenyl)propane, polymer with (chloromethyl)oxirane	N/Av	13600 mg/kg	> 4000 mg/kg
Phenol, 2,2'-methylenebis-, polymer with (chloromethyl)oxirane	N/Av	> 5000 mg/kg	> 6000 mg/kg
Alkyl (C12-14) glycidyl ether	N/Av	17100mg/kg	N/Av
Calcium Carbonate (Limestone)	N/Av	6450 mg/kg	N/Av
Crystalline Silica, Quartz	N/Av	N/Av	N/Av

Skin corrosion/irritation	: May cause irritation.
Serious eye damage/eye irritation	: Strong eye irritant.
Respiratory or skin sensitization	: Contains a component which is known to cause skin sensitization reactions. Does not contain known respiratory sensitizers.
Germ cell mutagenicity	: None known.
Carcinogenic status	: Contains a small amount of crystalline silica, or quartz, which is listed as a carcinogen via inhalation by IARC (Group 1), ACGIH (Group A2), NTP (Group 1) and OSHA (OSHA Select carcinogen).
Reproductive toxicity	: None known.
Specific Target Organ Toxicity, Single	Exposure
	: None known.
Specific Target Organ Toxicity, Repe	ted Exposure
	: None known.
Aspiration hazard	: None known.
Other important hazards	: See Section 2 for additional information.

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects

: The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

Important environmental characteristics

:	N/Av
Ecotoxicological :	No data is available on the product itself.
Persistence and degradability :	Not Available.
Bioaccumulative potential :	Not Available.
Mobility in the soil :	Not Available
PBT and vPvB assessment :	Not Available
Other adverse effects :	Not Available

SECTION 13 – DISPOSAL CONSIDERATION

Handling for disposal : Methods of disposal :	Handle waste according to recommendations in Section 7. Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA. You must test your waste using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
RCRA :	If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification

and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN 3082	Environmentally hazardous substances, liquid, n.o.s. (Contains: 2,2-bis(4-hydroxyphenyl)propane, polymer with (chloromethyl)oxirane; Phenol, 2,2'- methylenebis-, polymer with (chloromethyl)oxirane)	9	111	3082
TDG Additional Information	None				
49 CFR/DOT	UN 3082	Environmentally hazardous substances, liquid, n.o.s. (Contains: 2,2-bis(4-hydroxyphenyl)propane, polymer with (chloromethyl)oxirane; Phenol, 2,2'- methylenebis-, polymer with (chloromethyl)oxirane)	9	111	3082
49 CFR/DOT Additional Information	None				

Marine Pollutant

: Yes

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Immediate (Acute) Health Hazard

Chronic Health Hazard.

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

U.S. State Right To Know Laws

California Proposition 65: Warning! This product contains a chemical known to the State of California to cause cancer.

Other State Right to Know Laws: The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Calcium Carbonate	1317-65-3	No	Yes	Yes	Yes	Yes	Yes
Quartz	14808-60-7	No	Yes	Yes	Yes	Yes	Yes

	SECTION 16 – OTHER INFORMATION
HMIS Rating	: <u>* - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe</u> Health: *2 Flammability 1 Physical Hazard 0 PPE: Gloves, safety glasses
Legend	: ACGIH: American Conference of Governmental Industrial Hygienists
	CAS: Chemical Abstract Services
	CERCLA: Comprehensive Environmental Response, Compensation, and Liability
	Act of 1980
	CFR: Code of Federal Regulations
	DOT: Department of Transportation
	DSL: Domestic Substances List
	EPA: Environmental Protection Agency
	GHS: Globally Harmonized System
	HPR: Hazardous Products Regulations
	IARC: International Agency for Research on Cancer
	Inh: Inhalation
	N/Av: Not Available
	N/Ap: Not Applicable
	NIOSH: National Institute of Occupational Safety and Health
	NTP: National Toxicology Program
	OSHA: Occupational Safety and Health Administration
	PEL: Permissible exposure limit
	RCRA: Resource Conservation and Recovery Act
	SARA: Superfund Amendments and Reauthorization Act
	STEL: Short Term Exposure Limit
	TDG: Canadian Transportation of Dangerous Goods Act & Regulations TLV: Threshold Limit Values
	TSCA: Toxic Substance Control Act
	TWA: Time Weighted Average
	WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. ARDEX Engineered Cements will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By: ARDEX Engineered Cements 400 Ardex Park Drive Aliquippa, PA, U.S.A. 15001

(724) 203-5000 Visit our Website: http://www.ardexamericas.com

Revision date:

: 06-Mar-2015

End of Document